

SC to LC UPC, Fiber Patch Cord, 1.6 mm Duplex, Plenum



Ordering Details

| Part Number | Jacket Color | Breakout Length | Cable Glands | Pulling Grips, qty | Length |
|-------------|--------------|-----------------|--------------|--------------------|--------|
| SLDM | Orange | N/A | No glands | 0 | 3 m |

↳ *SC to LC UPC, Fiber Patch Cord, 1.6 mm Duplex, Plenum, Orange jacket, 3 m*

Construction Materials

Fiber Type zero water peak multimode fiber
 (850/1300: 3.0/1.0 dB/km | OM2) Total Fibers, quantity 2

Dimensions

Cord Length, maximum 999 ft | 999 m Cord Length, minimum 2.56 ft | 2 m Diameter Over Jacket 1.60 mm | 0.06 in

Ordering Note For lengths greater than 999 ft (304 m), orders must be in meters | Minimum length may vary based on cable configuration

Environmental Specifications

Environmental Space Plenum
 Operating Temperature -40 °C to +85 °C (+40 °F to +185 °F)

General Specifications

| | |
|--------------------------------|-------------------|
| Color, connector A | Blue Color |
| Connector B | Blue |
| Construction Type | Duplex patch cord |
| Interface, connector A | SC |
| Interface, connector B | LC |
| Interface Feature, connector A | Standard |
| Interface Feature, connector B | UPC |

Mechanical Specifications

Cable Retention Strength, maximum 4.40 lb @ 90 °
11.24 lb @ 0 °

Regulatory Compliance/Certifications

| Agency | Classification |
|-----------------|--|
| RoHS 2002/95/EC | Compliant |
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |

